


150W, the specification and parameter table

Functional project	name	A 1		remarks
		Portable energy storage power supply	B AB	
surface	product photograph			
Conventional parameters	internal battery	High energy density lithium battery		
	battery capacity	145Wh / 39000mAh /3.7V		
	Charging specifications	DC 15V /2.0A		
	Solar energy charging specifications	DC 35135 13V ~22V /2.0A		
	Charging time	DC: 7 hours		
	DC output	3 xDC output: 9~12.6V / 10A USB output: 5V / 2A + USB output 5V / 1A		
	AC AC output	The 2 xAC correction wave output		
	AC continuous output power	150W		
	LED lamp	2W		
	working temperature	-10℃-40℃		
	cycle life	And> 1,000 times		
	product protection	a .short-circuit protection b .overcurrent protection c .overvoltage crowbar d .undervoltage protection e .overload protection f . Overtemperature protection		
packing list	1 x portable emergency energy storage power supply 1 x recharger 1 x use manual 1x cigarette lighter 1x car charge			
Adapter parameters	output	15V 2A		
	DC joggle	35135		
	form	Wall charging type		
Enter the charging	Support for power adapter charging	support		
	Support for solar	support		

function	panel charging				
	Support for on-board charging	support			
cell	Battery model number and specification	18650			
	Individual cell capacity	2600MAH			
	Battery string and	3 String 5 and			
	Cell voltage	3V.7			
	battery voltage	11V.1			

structure	product size CM	19.8*10.8*12.6CM			
	Net weight of products	About 1.5kg			
	material quality	ABS plastic cement			
product packaging	Product packaging method	Express box			
	Cartridge size	28.2*14.6*17cm			
	Single hand-held case weight	2KG			
	carton size	580*460*20cm			
	Number of outer boxes	6PCS /CTN			
	tare	12.6kg			
Use the scene mode	Suitable for power outage, outdoor operation, night market electricity, emergency relief necessary, medical treatment, home energy storage and other power supply				